



Multnomah County Bike and Pedestrian Advisory Committee

Department of Community Services
Transportation Division

July 8, 2020

Project Overview

Purpose and Need



Seismic Resiliency and Emergency Response




Regional Recovery and Rebuilding



Long-term Use



Project Timeline




Funding

- Metro Get Moving 2020
- Vehicle Registration Fee



Key Milestones

Environmental Review Phase – Key Milestones




LEGEND
 CTF: Community Task Force
 PA: Preferred Alternative
 EIS: Environmental Impact Statement



Process Overview

STEPS IN GETTING TO A PREFERRED ALTERNATIVE (PA)




Range of Alternatives



**Enhanced
Seismic Retrofit**




**Replacement
Short Span**
(Bascule or Lift)



**Replacement
Long Span**
(Bascule or Lift)



**Replacement
Couch Extension**
(Bascule or Lift)




(Concept Images)

CTF Recommendation

Preferred Alternative

Replacement, Movable: Long Span Alternative



The example image above is just one variation of what a long span bridge could look like.

CTF Recommendation

Preferred Alternative: Replacement – Long Span

What we heard from CTF:



Best for seismic resiliency - locating fewer columns in liquefiable soils gives it the least risk from soil movement during an earthquake



It is the lowest cost of four build alternatives (\$825 million compared to as high as \$950 million for the most expensive option)



The reduced number of columns also benefits Waterfront Park users, crime prevention, and preservation of the Burnside Skatepark



Additional deck width over the river provides a safer facility for bicyclists, pedestrians and other users




Reduced impacts to natural resources due to fewer columns in the water



Explore ways to mitigate the long span's impacts on views




Project Cost by Alternative




Columns in dangerous soil


Replacement
Long Span




Replacement
Short Span



Replacement
Couch Extension



Enhanced
Seismic Retrofit



Less columns in parks



Replacement Long Span




Replacement Short Span and Couch Ext.




Enhanced Seismic Retrofit

Cross Sections

Retrofit



Replacements



Replacement, Movable: Long Span

Bridge Type Examples

BRIDGE TYPE OPTION: Tied Arch examples



Hastings Bridge, Minnesota



Torikai Ohas Bridge, Japan



Siuslaw River Bridge, Oregon



Tacony-Palmyra Bridge, Pennsylvania



Gateway Bridge, Michigan

BRIDGE TYPE OPTION: Cable Stayed examples



Indian River Inlet Bridge, Delaware



Chongqing Expressway Bridge



Copper River Bridge



Tilikum Crossing Bridge, Oregon

BRIDGE TYPE OPTION: Through Truss examples



Main Street Bridge, Florida



Triboro (Harlem River) Bridge



Tower Bridge, CA



Broadway Bridge



Hawthorn Bridge

MOVABLE SPAN: Bascule examples



South Park Bridge



Harbor Bridge, Spain



New Johnson St. Bridge, Canada



Woodrow Wilson Bridge

MOVABLE SPAN: Vertical Lift examples



Teregganu Bridge



Fore River Bridge



Pont Jacques Chaban - Delmas




Manchester Millenium Bridge, England

For information about this project in other languages, please call 503-209-4111 or email burnsidebridge@multco.us. | Para obtener información sobre este proyecto en español, ruso u otros idiomas, llame al 503-209-4111 o envíe un correo electrónico a burnsidebridge@multco.us. | Для получения информации об этом проекте на испанском, русском или других языках, свяжитесь с нами по телефону 503-209-4111 или по электронной почте: burnsidebridge@multco.us.


Range of Alternatives

Traffic Options During Construction



Preferred Alternative

Traffic During Construction: Full Bridge Closure




What we heard from CTF:

- **Least cost** - the temporary bridge would add \$90 million to the project cost
- **Shortest construction duration** (the temporary bridge would add 1.5 years to construction duration, extending duration of impacts to surrounding area including parks, residents, recreational activities and transportation)
- Least in-water construction which **reduces impact to natural resources**



Construction Timeline

PROJECT DURATION (Years)



Traffic Analysis

Full Bridge Closure:

- **Drivers:** ~2-4 minute delay
- **Bicyclists:** ~5-12 minute delay
- **Pedestrians:** ~10-18 minute delay
- **Buses:** ~5 min travel delay

The analysis evaluated the following temporary bridge types:

- All modes
- Bike/Ped/Transit only
- Bike/Ped only






The CTF did not feel the travel time savings justified the cost, added construction duration and impacts to natural resources.



...however, they strongly supported mitigation techniques to address safety and access



Demand management strategies would be developed during design

Summer Outreach

- Online Open House
- Briefings
- Virtual Tours and Animations
- Diverse Outreach (CEL Program)



Upcoming Meetings & Next Steps

- July: MultCo Board of County Commissioners briefing
- **August: Public Outreach on recommended PA**
- September: CTF & SASG
- October 2: Policy Group PA Recommendation Approval
- October: CTF – Kickoff Type Selection Phase
- January: Draft Environmental Impact Statement Publication



Questions?

